AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the

application:

**LISTING OF CLAIMS:** 

1. (Currently amended) A [[M]]method of backing up personal data of a

wireless communication network subscriber, the personal data being memorised in a

mobile communication device and backed up in a network server, in which a first

subset of data is prepared from among a batch of data to be backed up and is

transmitted to the server for backing up,

wherein said method includes an asynchronous backup mode in which, once

a subset has been transmitted to the server, the backup is delayed by a certain

period of time so as to free the mobile device for the user, and the backup is

resumed at the end of this period.

2. (Currently amended) The [[M]]method according to claim 1, wherein, in

order to resume the backup, the server implements a countdown of the period and

sends a resume signal to a chip card in the mobile device at the end of said period.

3. (Currently amended) The [[M]]method according to claim 1, wherein, in

order to resume the backup, the mobile device implements a countdown of the

period and sends a resume signal to a chip card in the mobile device at the end of

said period.

Attorney's Docket No. 1032326-000394

Application No. 10/583,476 Page 3

4. (Currently amended) The [[M]]method according to claim 3, wherein

the mobile implements the countdown and sends the resume signal upon receiving

an instruction from the chip card.

5. (Currently amended) The [[M]]method according to claim 4, wherein

the chip card gives instructions to the mobile device by means of Subscriber Identity

Module toolkit ("STK") commands.

6. (Currently amended) The [M]method according to claim 4, wherein

the chip card gives instructions by means of "GET STATUS" commands.

7. (Currently amended) The [[M]]method according to claim 1, further

comprising a prior assessment step which determines whether the volume of data to

be backed up or the corresponding waiting time required to make the mobile device

available to the user is higher than a predetermined threshold,

- if so, the backup is performed according to the asynchronous backup

mode,

- and if not, the backup is carried out according to a default mode.

8. (Currently amended) A [[S]]server for backing up personal data of a

wireless communication network subscriber, the personal data having been

previously memorised in a mobile communication device, said server capable being

able to of backing up a first subset of data from among a batch of data to be backed

up,

said server including an asynchronous server backup program that <u>is</u>

<u>capable of [[can]] implementing the following functions:</u>

- receiving and saving a subset of data and entering a waiting mode according to a delay instruction,
- and, at the end of the delay instruction, resuming the backup of the subsequent subsets of data.
- 9. (Currently amended) <u>A</u> [[P]]portable wireless communication device belonging to a communication network subscriber, comprising memorised data and a "device" backup application that <u>is capable of</u> [[can]] transmitting a first subset of data from among a batch of data to be backed up to the server for backing up,

wherein the device application is capable of [[can]], according to an asynchronous backup mode:

- delaying by a given period of time the backup of a subset of data that is subsequent to the first subset, so as to ensure that the user can use the device,
  - and resum[[e]]ing the backup at the end of the period.
- 10. (Currently amended) A [[P]]portable device according to claim 9, wherein said device selectively operates according to an asynchronous backup mode and a normal mode.
- 11. (New) A method of backing up personal data of a wireless communication network subscriber, the personal data being memorised within a mobile communication device and backed up within a network server,

Attorney's Docket No. 1032326-000394

Application No. 10/583,476

Page 5

wherein said method includes an asynchronous backup mode in which, once

the mobile communication device has prepared a first subset of data from among a

batch of data to be backed up and transmitted the first subset of data to a network

server for backing up, the backup is delayed by a predetermined period of time, so

as to free the mobile communication device for a user of the mobile communication

device, and the backup of at least one subset of data subsequent to the first subset

of data is resumed at the end of said predetermined period of time.

12. (New) The method according to claim 11, wherein, in order to resume

the backup, the network server implements a countdown of a period of time and

sends a resume signal to a chip card in the mobile communication device at the end

of said predetermined period of time.

13. (New) The method according to claim 11, wherein, in order to resume

the backup, the mobile communication device implements a countdown of a period

of time and sends a resume signal to a chip card in the mobile device at the end of

said predetermined period of time.

14. (New) The method according to claim 13, wherein the mobile

communication device implements the countdown and sends the resume signal

upon receiving an instruction from the chip card.

15. (New) The method according to claim 14, wherein the chip card gives

said instruction to the mobile communication device by sending it a Subscriber

Identity Module toolkit ("STK") command.

16. (New) The method according to claim 14, wherein the chip card gives

said instruction to the mobile communication device by sending it a "GET STATUS"

command.

17. (New) The method according to claim 11, further comprising a prior

assessment step in which a volume of data to be backed up or a corresponding

waiting time required to make the mobile communication device available to the user

is determined and compared to a predetermined threshold,

- when the volume of data is higher than the predetermined threshold, the

backup is performed according to the asynchronous backup mode 40,

- and, when the volume of data is not higher than the predetermined

threshold, the backup is carried out according to a default mode.

18. (New) A server for backing up personal data of a wireless

communication network subscriber, the personal data having been previously

memorised within a mobile communication device,

wherein said server comprises means for backing up a first subset of data

from among a batch of data to be backed up, and

said means for backing up data is arranged, according to an asynchronous

mode, to:

Page 7

- receive and save the first subset of data and entering a waiting time mode

according to a delay instruction,

- and, at the end of the waiting time, resuming the backup of at least one

subset of data subsequent to the first subset of data.

19. A portable communication device belonging to a wireless (New)

communication network subscriber, said portable communication device comprising

at least one memory for memorizing data,

wherein said portable communication device comprises means for backing up

data, said means for backing up data transmitting a first subset of data from among a

batch of data to be backed up to a server for backing up, and

said means for backing up data is arranged, according to an asynchronous

backup mode, to:

- delay by a predetermined period of time the backup of at least one subset of

data that is subsequent to the first subset of data, so as to ensure that a user of the

portable communication device may use the portable communication device,

- and resume the backup of at least one subset of data subsequent to the first

subset of data at the end of the predetermined period of time.

20. (New) The portable communication device according to claim 19,

wherein said portable communication device selectively operates according to an

asynchronous backup mode and a normal mode.